



TEMPEX

Xpress

Express high-performance basic cleaner & stripper for hard floor coverings

Area of application

Pleasantly perfumed, low-foaming, high-performance basic cleaner. Can be used on all water-resistant, alkali-sensitive and alkali-resistant hard floor coverings. Removes all types of polymer dispersions. Works efficiently and quickly, even on strongly adhering, over-treated, aged or multi-coated floor coverings.

Application

For machine-based basic cleaning and stripping, first remove coarse dirt from the floor. Depending on age, the number of applications and type of coating, mix with cold water at a ratio of 1:2, 1:3 or 1:4. (2-4 liters of TEMPEX Xpress + 8 liters of water). Apply cleaning solution (500-650 ml/m²), exposure time 10 min., for strongly adhering coatings up to max. 30 min. Then machine-work the entire surface with a single-disc machine and a suitable PAD/brush. Thoroughly vacuum off the dirty liquor and clean the surface with clear water. In the case of heavily aged and multi-coatings, increase the exposure time and dosage according to the information on the label/product data sheet.

For linoleum coverings, an intermediate sanding is recommended after the basic cleaning for smoothing. In the case of older, open-pored or pre-damaged floor coverings, in particular linoleum coverings, the depth-effective effect of TEMPEX XPRESS is intensified, so that linseed oils and resins are transported to the surface. This is visually similar to a discoloration or saponification of the coating – this effect is equalized in the time frame of the thorough drying of the coating.

Do not use in confined spaces. Deactivate ventilation systems and ensure fresh air supply!

Product characteristics

- Excellent material compatibility on all waterproof, alkali-sensitive floor coverings
- Efficient and effortless removal of even stubborn polymer protective films
- Short working times due to extremely fast and efficient dissolving behaviour (exposure time 10 min.)
- Leaves no glossy islands, but an evenly matt surface that is ideal for coating
- Low-foaming formulation suitable for automatic cleaning machines
- No neutralization required by flooding the surface with clear water
- Low Volatile Organic Compounds (VOC) - Content
- The formulation is free of 2-butoxyethanol (butyl glycol)
- Pleasant fragrance during handling

Hinweis

Note: Before use, check material compatibility on an inconspicuous spot. Make sure there is enough fresh air during and after use. Do not use in confined spaces. For commercial use only. Only recycle packaging when completely empty. Dispose of any remaining product as required.

Technical information

10 litre canister

order No. DR500552



All information contained in our brochures is accurate to the best of our knowledge and experience. No liability can be derived from the information herein. For details about the product, please refer to the safety data sheet.  0722

pH conc

0	2	4	6	8	12	14
---	---	---	---	---	----	----

DR.SCHNELL GmbH & Co. KGaA
 Taunusstraße 19 · 80807 Munich
 Tel. +49 89 3506080
 info@dr-schnell.com
 www.dr-schnell.com

Wir leben Hygiene
DR.SCHNELL
 QUALITÄT UND SERVICE